

# LOOK™ Classic No Etch

## Integrated LED Illuminated Mirror




### Features

- Improved illumination and reduced shadowing through the use of side lighting
- Illumination from the back provides an ambient glow
- Mirror and mounting panel is IP44 rated
- Detailed dimensional drawings are available for all mirrors to help in planning the layout of blocking and power supply location.
- Safety PVC membrane on back prevents small pieces from falling off in the event of a mirror breakage
- Copper-free backing for greater corrosion and scratch resistance
- Can be mounted either portrait or landscape orientation
- Back box power supply provides flexible installation that meets stringent building codes
- Power supply junction box can be screwed into the pre-installed brackets on the mirror or into contractor supplied blocking

### Specification Guide

**Sample Part #: 694NE1830-30KSO00B**



Base Part #	Size	Color Temp.	Output
694NE	1830 - 18"W x 30"H 1824 - 18"W x 24"H 2436 - 24"W x 36"H 3927 - 39"W x 27"H 2442 - 24"W x 42"H 3042 - 30"W x 42"H	30 - 3000K 35 - 3500K* 40 - 4000K*	SO00B - Standard HO00B - High*

\* Non-stock option, subject to a 50 piece minimum order quantity, contact sales for availability.




## Product Details

Part #	694NE1830-KKXX00B	694NE1824-KKXX00B	694NE2436-KKXX00B	694NE3927KK00B	694NE2442-KKXX00B	694NE3042-KKXX00B
Dimensions	18"W x 30"H x 1.7"D	18"W x 24"H x 1.7"D	24"W x 36"H x 1.7"D	39"W x 27"H x 1.7"D	24"W x 42"H x 1.7"D	30"W x 42"H x 1.7"D
Housing	Anodized Aluminum	Anodized Aluminum	Anodized Aluminum	Anodized Aluminum	Anodized Aluminum	Anodized Aluminum
Lens	Glass	Glass	Glass	Glass	Glass	Glass
Wattage	19W	17W	24W	26W	26W	29W
Voltage	24V	24V	24V	24V	24V	24V
Current	0.19A	0.17A	0.24A	0.26A	0.26A	0.29A
Lumens	2000 LM	1840LM	2640LM	2900LM	2900LM	3165LM
Kelvin	3000K, 3500K <sup>2</sup> or 4000K <sup>2</sup>	3000K, 3500K <sup>2</sup> or 4000K <sup>2</sup>	3000K, 3500K <sup>2</sup> or 4000K <sup>2</sup>	3000K, 3500K <sup>2</sup> or 4000K <sup>2</sup>	000K, 3500K <sup>2</sup> or 4000K <sup>2</sup>	3000K, 3500K <sup>2</sup> or 4000K <sup>2</sup>
CRI	> 90	> 90	> 90	> 90	> 90	> 90

## Power Box Specifications

\*\*Ordered Separately



Part Number	690010.121 0-10V DC	690010.143* Line Voltage
Dimensions	13"L x 1.25"W x 1.7"D	
Housing	Aluminum	
Wattage	96W	
Voltage	120 - 277V AC	
Current	Max 4A	
Power Factor	0.94 @ 120V AC	
Frequency	50 - 60Hz	

### Line Voltage Approved Dimmers

Leviton		Lutron	
VPI06-1LZ	DZ6HD	SCL-153PR	CTCL-153PDH
TTI06-1LZ	6674	DVCL-153PR	PD-6WCL
IPL06	6672	DVWCL-153PH	PD-5NE-WH

- Notes:**
1. Lumens per watt based on light source
  2. Standard non-stock mirrors subject to 90 day lead time
  3. Custom mirrors available upon request, subject to a 50 piece minimum, 50% deposit and 90 day lead time following approved drawings
  4. Mirrors must be shipped LTL and cannot be shipped via FedEx or UPS
  5. Warranty: 10-year frame and structure - 7-year glass, power supply and LEDs

