## Solstice<sup>™</sup> Diffused Flexible LED Light



### **Features**

- · An economical flexible light designed specifically for indirect lighting applications like under cabinets
- Soft and appealing light output with neon lighting-like illumination
- · Available in custom lengths up to 200"
- Multiple color options including white, warm white, cool white, Blue, Green, Red and Amber
- Standard IP66 rated and UV stable for installation in damp, wet or exterior locations. IP67 available upon request
- · 30,000 hours of estimated life
- Decorative stainless steel or white plastic end caps available for a more finished look


## **Product Details**


Housing Material	Diffused Silicone		
Voltage	12-14V DC		
Wattage	1.6W/Ft		
Current	0.12A/Ft		
Lumens	115LM/Ft @ 6300K 100LM/Ft @ 3000K 25LM/Ft @ Blue 40LM/Ft @ Red		
Color Temp.	3000K, 3500K, 4000K, 6300K, Blue, Green, Amber or Red		
Wire Gauge	18 AWG		
IP Rating	IP66 or IP67		
UV Stable	Yes		

## **Specification Guide**

# Sample Part #: RRLL1230-20012-10 Base Part # Voltage Voltage

Base Part #	Voltage	LED Color	Light Length	Wire Length	Light Width
RRLL	12 - 12V	30 - 3000K 35 - 3500K 40 - 4000K 63 - 6300K BL - Blue GR - Green RD - Red AM - Amber	200 - 200 in. Max *cuts every inch	12 - 12 in. Stnd Length	10 - 10mm







## **Accessory Specification**

Description	Part #			
RGB Channel				
Aluminum Straight Mount Track Without Tape	RNLL-1-72			
Aluminum Straight Mount Track With Tape	RNLL-1T-72			
Aluminum 45° Mount Track Without Tape	RNLL-2-72-CL			
Aluminum 45° Mount Track With Tape	RNLL-2T-72			
Black Plastic Straight Mount Track Without Tape	RBLL-2			
Black Plastic Straight Mount Track With Tape	RBLL-1			
White Plastic Straight Mount Track Without Tape	RBLL10-KS			
White Plastic Straight Mount Track With Tape	RBLL10-KT			





Description	Part #
IP67 Wire End Cap	440-00335
IP67 Finished End Cap	440-00336
Decorative Stainless Steel End Cap Kit	RNLL-SS-CAP
Decorative White Plastic End Cap (For use in wood and fiberglass only)	810-00247