Piper™ 2.0 Front Cap Flex Light





Features

- Co-extruded silicone housing withstands wind and water spray, such as that experienced on the front of a vehicle
- · Available in bulk rolls or custom cut lengths
- Available in warm white, cool white, blue, red, green, or amber
- Includes easy to install adhesive backing for quick and durable installation
- Plastic mounting channels available with or without 3M 9495LE adhesive backing
- · IP64 rated for water resistant applications

Product Details

Voltage	10-14V DC			
Wattage	1.1W/Ft			
Current	0.12A/Ft			
Lumens	80LM/Ft			
Color Temp.	3000K, 3500K, 4000K, 6300K, Blue, Red, Green or Amber			
IP Rating	IP64			
UV Stable	Yes			
Wire Gauge	18 AWG			

Specification Guide

Sample Part #:	TP	Q12	230-	700)12	-8
-	:	:	:	:	:	:
	•	:	:	:	:	:
Base Part # · · · · · · · · · · · · · · · · · ·	· · · · · :	÷	:	÷		
Voltage ·····		:	÷	÷		
Color Temperature			:	÷		:
Light Length				:		:
Wire Length					:	:

Light Width ······

Base Part #	Voltage	Color Temp.	Light Length	Wire Length	Light Width
TPQ	12 - 12V	30 - 3000K 35 - 3500K 40 - 4000K 63 - 6300K BL - Blue RD - Red GR - Green AM - Amber	700 - 700cm	12 - 12"	8 - 8mm

Note: Light cannot be field cut, contact sales for information on custom lengths

TPB-1:72" Black Palstic Screw Mount Channel

TPB-2:72" Clear Plastic Adhesive Mount Channel